

Sulphur hexafluoride

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Reference number: 110 Revision date: 21/02/2023 Supersedes version of: 29/11/2021

Warning



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : Sulphur hexafluoride

SDS no : 110

Other means of identification : Sulphur hexafluoride

CAS-No. : 2551-62-4 EC-No. : 219-854-2

EC Index-No. : --

REACH registration No : 01-2119458769-17

Chemical formula : SF6

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : Industrial and professional uses. Perform risk assessment prior to use.

Test gas/Calibration gas. Chemical reaction / Synthesis.

Laboratory use.

Use for manufacture of electronic/photovoltaic components.

Contact supplier for more information on uses. Industrial use. Perform risk assessment prior to use.

Uses advised against : Do not inhale product on purpose because of the risk of asphyxiation.

Uses other than those listed above are not supported, contact your supplier for more

information on other uses.

1.3. Details of the supplier of the safety data sheet

Company identification : SOL SpA

Via G. Borgazzi 27 20900 MONZA - Italia T +39 039 23.96.1 http:\\www.sol.it msds@sol.it

msds@sol.it : msds@sol.it

E-Mail address (competent person)

1.4. Emergency telephone number

Emergency telephone number : Linea verde SET - 800452661 (24h/24h, 365 giorni l'anno); Dall'estero +39 0283421263

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Physical hazards Gases under pressure : Liquefied gas H280



Sulphur hexafluoride

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Reference number: 110

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP) : Warning

Hazard statements (CLP) : H280 - Contains gas under pressure; may explode if heated.

Precautionary statements (CLP)

- Storage : P403 - Store in a well-ventilated place.

Supplemental information : Do not inhale product on purpose because of the risk of asphyxiation.

Contains fluorinated greenhouse gases listed in Annex I of EU 517/2014 as amended.

2.3. Other hazards

Asphyxiant in high concentrations.

Contact with liquid may cause cold burns/frostbite.

SECTION 3: Composition/information on ingredients

3.1. Substances

| Name | % | Product identifier | Classification according to Regulation (EC) No. 1272/2008 [CLP] |
|----------------------|-----|---|---|
| Sulphur hexafluoride | 100 | CAS-No.: 2551-62-4 EC-No.: 219-854-2 EC Index-No.: REACH registration No: 01- 2119458769-17 | Press. Gas (Liq.), H280 |

Contains no other components or impurities which will influence the classification of the product.

3.2. Mixtures

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

- Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep

victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing

stopped.

- Skin contact : In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Obtain

medical assistance.

- Eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes.

- Ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

In high concentrations may cause asphyxiation. Symptoms may include loss of

mobility/consciousness. Victim may not be aware of asphyxiation.

See section 11.

$\underline{\textbf{4.3. Indication of any immediate medical attention and special treatment needed}}$

None.

SOL SpA EN (English) 2/10 Via G. Borgazzi 27 20900 MONZA Italia, +39 039



Sulphur hexafluoride

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Reference number: 110

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray or fog.

Product does not burn, use fire control measures appropriate for the surrounding fire.

- Unsuitable extinguishing media : Do not use water jet to extinguish.

5.2. Special hazards arising from the substance or mixture

Specific hazards : Exposure to fire may cause containers to rupture/explode.

Hazardous combustion products : Hydrogen fluoride. Sulphur dioxide.

5.3. Advice for firefighters

Specific methods : Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat

radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering

sewers and drainage systems. If possible, stop flow of product.

Use water spray or fog to knock down fire fumes if possible.

Move containers away from the fire area if this can be done without risk.

Special protective equipment for fire fighters : In confined space use self-contained breathing apparatus.

Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire

fighters.

Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full

face mask.

Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves

for firefighters.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : Act in accordance with local emergency plan.

Try to stop release. Evacuate area.

Ensure adequate air ventilation.

Prevent from entering sewers, basements and workpits, or any place where its

accumulation can be dangerous.

Stay upwind.

See section 8 of the SDS for more information on personal protective equipment.

For emergency responders : Wear self-contained breathing apparatus when entering area unless atmosphere is proved

to be safe.

Oxygen detectors should be used when asphyxiating gases may be released.

See section 5.3 of the SDS for more information.

6.2. Environmental precautions

Try to stop release.

6.3. Methods and material for containment and cleaning up

Ventilate area.

6.4. Reference to other sections

See also sections 8 and 13.

SOL SpA Via G. Borgazzi 27 20900 MONZA Italia, +39 039 23.96.1 EN (English)

3/10



Sulphur hexafluoride

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Reference number: 110

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Safe handling of the gas receptacle

Safe use of the product

: The product must be handled in accordance with good industrial hygiene and safety procedures

Only experienced and properly instructed persons should handle gases under pressure.

Consider pressure relief device(s) in gas installations.

Ensure the complete gas system was (or is regularily) checked for leaks before use.

Do not smoke while handling product.

Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.

Avoid suck back of water, acid and alkalis.

Do not breathe gas.

Avoid release of product into work area.

Refer to supplier's container handling instructions.

Do not allow backfeed into the container.

Protect containers from physical damage; do not drag, roll, slide or drop.

When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.

Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.

If user experiences any difficulty operating valve discontinue use and contact supplier.

Never attempt to repair or modify container valves or safety relief devices.

Damaged valves should be reported immediately to the supplier.

Keep container valve outlets clean and free from contaminants particularly oil and water.

Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.

Close container valve after each use and when empty, even if still connected to equipment.

Never attempt to transfer gases from one cylinder/container to another.

Never use direct flame or electrical heating devices to raise the pressure of a container.

Do not remove or deface labels provided by the supplier for the identification of the content

of the container

Suck back of water into the container must be prevented.

Open valve slowly to avoid pressure shock.

7.2. Conditions for safe storage, including any incompatibilities

Observe all regulations and local requirements regarding storage of containers.

Containers should not be stored in conditions likely to encourage corrosion.

Container valve guards or caps should be in place.

Containers should be stored in the vertical position and properly secured to prevent them

from falling over.

Stored containers should be periodically checked for general condition and leakage.

Keep container below 50°C in a well ventilated place.

Store containers in location free from fire risk and away from sources of heat and ignition.

Keep away from combustible materials.

7.3. Specific end use(s)

None.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| Sulphur hexafluoride (2551-62-4) | | | | |
|--|------------|--|--|--|
| DNEL: Derived no effect level (Workers) | | | | |
| Long-term - systemic effects, inhalation | 6074 mg/m³ | | | |

SOL SpA Via G. Borgazzi 27 20900 MONZA Italia, +39 039 23.96.1 EN (English)

4/10



Sulphur hexafluoride

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Reference number: 110

| Sulphur hexafluoride (2551-62-4) | | | | |
|---|-----------|--|--|--|
| PNEC: Predicted no effect concentration | | | | |
| Aqua (freshwater) | 0.15 mg/l | | | |
| Aqua (marine water) | 1.5 mg/l | | | |

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Systems under pressure should be regularily checked for leakages.

Ensure exposure is below occupational exposure limits (where available).

Oxygen detectors should be used when asphyxiating gases may be released.

Consider the use of a work permit system e.g. for maintenance activities.

8.2.2. Individual protection measures, e.g. personal protective equipment

A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk.

The following recommendations should be considered:

PPE compliant to the recommended EN/ISO standards should be selected.

Eye/face protection
 Wear goggles when transfilling or breaking transfer connections.

Standard EN 166 - Personal eye-protection - specifications.

Skin protection

- Other

- Hand protection : Wear working gloves when handling gas containers.

Standard EN 388 - Protective gloves against mechanical risk, performance level 1 or higher.

Wear cold insulating gloves when transfilling or breaking transfer connections.

Standard EN 511 - Cold insulating gloves.

: Wear safety shoes while handling containers.

Standard EN ISO 20345 - Personal protective equipment - Safety footwear.

• Respiratory protection : Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full

race mask.

Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be

used in oxygen-deficient atmospheres.

• Thermal hazards : None in addition to the above sections.

8.2.3. Environmental exposure controls

Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for

specific methods for waste gas treatment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

- Physical state at 20°C / 101.3kPa
- Colour
: Gas.
- Colourless.
Odourless.

Odour threshold is subjective and inadequate to warn of overexposure.

Melting point / Freezing point : -50.8 °C

-50.8 °C -64 °C

Boiling point : -64 °C

Flammability : Non flammable.

Lower explosion limit : Not available

Upper explosion limit : Not available

Flash point : Not applicable for gases and gas mixtures.

Auto-ignition temperature : Non flammable.

Decomposition temperature : Not applicable.

pH : Not applicable for gases and gas mixtures.



Sulphur hexafluoride

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Reference number: 110

Viscosity, kinematic : No reliable data available.

Water solubility [20°C] : 41 mg/l
Partition coefficient n-octanol/water (Log Kow) : Not available
Vapour pressure [20°C] : 21 bar(a)
Vapour pressure [50°C] : Not applicable.
Density and/or relative density : Not applicable.

Relative vapour density (air=1) : 5

Particle characteristics : Not applicable.

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Explosive properties : Not applicable.

Explosion limits : Non flammable.

Oxidising properties : Not applicable.

Critical temperature [°C] : 45.5 °C

9.2.2. Other safety characteristics

Molar mass : 146 g/mol

Evaporation rate : Not applicable for gases and gas mixtures.

Gas group : Press. Gas (Liq.).

Other data : Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below

ground level.

SECTION 10: Stability and reactivity

10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Avoid moisture in installation systems.

10.5. Incompatible materials

None.

For additional information on compatibility refer to ISO 11114.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not

be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity : Toxicological effects not expected from this product if occupational exposure limit values are

not exceeded.

Skin corrosion/irritation : No known effects from this product.

Serious eye damage/irritation : No known effects from this product.

Respiratory or skin sensitisation : No known effects from this product.

Germ cell mutagenicity : No known effects from this product.

Carcinogenicity : No known effects from this product.

Toxic for reproduction : Fertility : No known effects from this product.

Toxic for reproduction : unborn child : No known effects from this product.

SOL SpA EN (English) 6/10
Via G. Borgazzi 27 20900 MONZA Italia, +39 039



Sulphur hexafluoride

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Reference number: 110

STOT-single exposure
STOT-repeated exposure

No known effects from this product.No known effects from this product.

: Not applicable for gases and gas mixtures.

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Aspiration hazard

Assessment : Classification criteria are not met.

EC50 48h - Daphnia magna [mg/l] : 247 mg/l

EC50 72h - Algae [mg/l] : No data available.

LC50 96 h - Fish [mg/l] : 236 mg/l

12.2. Persistence and degradability

Assessment : Not applicable for inorganic products.

12.3. Bioaccumulative potential

Assessment : Not expected to bioaccumulate due to the low log Kow (log Kow < 4).

See section 9.

12.4. Mobility in soil

Assessment : Because of its high volatility, the product is unlikely to cause ground or water pollution.

Partition into soil is unlikely.

12.5. Results of PBT and vPvB assessment

Assessment : Not classified as PBT or vPvB.

12.6. Endocrine disrupting properties

Assessment :

12.7. Other adverse effects

Other adverse effects : No known effects from this product. Effect on the ozone layer : No effect on the ozone layer.

Global warming potential [CO2=1] : 22800

Effect on global warming : When discharged in large quantities may contribute to the greenhouse effect.

Contains fluorinated greenhouse gases listed in Annex I of EU 517/2014 as amended.

For quantities refer to cylinder label.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Refer to supplier's waste gas recovery programme.

Contact supplier if guidance is required.

Discharge to atmosphere in large quantities should be avoided.

Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from local regulations or operating permits are not

exceeded.

Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at

http://www.eiga.org for more guidance on suitable disposal methods.

Return unused product in original container to supplier.

List of hazardous waste codes (from Commission Decision 2000/532/EC as amended)

16 05 04 *: Gases in pressure containers (including halons) containing hazardous substances

13.2. Additional information

External treatment and disposal of waste should comply with applicable local and/or national regulations.

SOL SpA EN (English) 7/10
Via G. Borgazzi 27 20900 MONZA Italia, +39 039

23.96.1



Sulphur hexafluoride

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Reference number: 110

SECTION 14: Transport information

14.1. UN number or ID number

In accordance with ADR / RID / IMDG / IATA / ADN

UN-No. : 1080

14.2. UN proper shipping name

Transport by road/rail (ADR/RID) : SULPHUR HEXAFLUORIDE

Transport by air (ICAO-TI / IATA-DGR) : Sulphur hexafluoride

Transport by sea (IMDG) : SULPHUR HEXAFLUORIDE

14.3. Transport hazard class(es)

Labelling

2.2 : Non-flammable, non-toxic gases.

Transport by road/rail (ADR/RID)

Class : 2
Classification code : 2A
Hazard identification number : 20

Tunnel Restriction : C/E - Tank carriage : Passage forbidden through tunnels of category C, D and E. Other

carriage: Passage forbidden through tunnels of category E

Transport by air (ICAO-TI / IATA-DGR)

Class / Div. (Sub. risk(s)) : 2.2

Transport by sea (IMDG)

Class / Div. (Sub. risk(s)) : 2.2
Emergency Schedule (EmS) - Fire : F-C
Emergency Schedule (EmS) - Spillage : S-V

14.4. Packing group

Transport by road/rail (ADR/RID) : Not applicable.

Transport by air (ICAO-TI / IATA-DGR) : Not applicable.

Transport by sea (IMDG) : Not applicable.

14.5. Environmental hazards

Transport by road/rail (ADR/RID) : None.
Transport by air (ICAO-TI / IATA-DGR) : None.
Transport by sea (IMDG) : None.

14.6. Special precautions for user

Packing Instruction(s)

Transport by road/rail (ADR/RID) : P200.

Transport by air (ICAO-TI / IATA-DGR)

Passenger and Cargo Aircraft : 200.
Cargo Aircraft only : 200.
Transport by sea (IMDG) : P200.

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's

compartment.

Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in

the event of an accident or an emergency. Before transporting product containers:

- Ensure there is adequate ventilation.

- Ensure that containers are firmly secured.
- Ensure valve is closed and not leaking.
- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
- Ensure valve protection device (where provided) is correctly fitted.

SOL SpA Via G. Borgazzi 27 20900 MONZA Italia, +39 039 23.96.1 EN (English) 8/10



Sulphur hexafluoride

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Reference number: 110

14.7. Maritime transport in bulk according to IMO instruments

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

Restrictions on use : Not allowed for magnesium die-casting. (Regulation (EU) No 517/2014).

Not allowed to be used for inflating tyres. (Regulation 517/2014).

Other information, restriction and prohibition

regulations

: Not listed on the PIC list (Regulation EU 649/2012).

Seveso Directive: 2012/18/EU (Seveso III) : Not covered.

National regulations

Regulatory reference : Ensure all national/local regulations are observed.

15.2. Chemical safety assessment

A CSA has been carried out.

SECTION 16: Other information

Indication of changes : Revised safety data sheet in accordance with commission regulation (EU) No 2015/830.

Abbreviations and acronyms : ATE - Acute Toxicity Estimate.

CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008.

REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation

(EC) No 1907/2006.

EINECS - European Inventory of Existing Commercial Chemical Substances.

CAS# - Chemical Abstract Service number. PPE - Personal Protection Equipment.

LC50 - Lethal Concentration to 50 % of a test population.

RMM - Risk Management Measures.

PBT - Persistent, Bioaccumulative and Toxic. vPvB - Very Persistent and Very Bioaccumulative.

STOT- SE: Specific Target Organ Toxicity - Single Exposure.

CSA - Chemical Safety Assessment.

EN - European Standard. UN - United Nations.

ADR - European Agreement concerning the International Carriage of Dangerous Goods by

Road.

IATA - International Air Transport Association.

IMDG code - International Maritime Dangerous Goods.

RID - Regulations concerning the International Carriage of Dangerous Goods by Rail.

WGK - Water Hazard Class.

STOT - RE: Specific Target Organ Toxicity - Repeated Exposure.

UFI : Unique Formula Identifier.

Training advice : The hazard of asphyxiation is often overlooked and must be stressed during operator

training.

For more guidance, refer to EIGA SL 01 "Dangers of Asphyxiation", downloadable at

9/10

http://www.eiga.eu..

Further information : Classification in accordance with the procedures and calculation methods of Regulation

(EC) 1272/2008 (CLP).

Key literature references and sources of data are maintained in EIGA doc 169 : 'Classification and Labelling Guide', downloadable at http://www.Eiga.eu .

| Full text of H- and EUH-statements | |
|------------------------------------|---|
| H280 | Contains gas under pressure; may explode if heated. |

SOL SpA EN (English)
Via G. Borgazzi 27 20900 MONZA Italia, +39 039



Sulphur hexafluoride

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Reference number: 110

| Press. Gas (Liq.) | Gases under pressure : Liquefied gas |
|-------------------|--------------------------------------|

DISCLAIMER OF LIABILITY

 Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.
 Details given in this document are believed to be correct at the time of going to press.
 Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

End of document